

# 4500 Wireless remote control

4500 Wireless Remote Control allows you to perform, with safety and precision, low-speed maneuvers such as docking, anchoring or mooring from the most convenient position of your boat



# Available configurations



## WRC 3F

- PORT ENGINE
- STARBOARD ENGINE
- BOW THRUSTER



## WRC 4F

- PORT ENGINE
- STARBOARD ENGINE
- BOW THRUSTER
- STERN THRUSTER



## WRC 5F

- PORT ENGINE
- STARBOARD ENGINE
- BOW THRUSTER
- ANCHOR WINCH



## WRC 6F

- PORT ENGINE
- STARBOARD ENGINE
- BOW THRUSTER
- STERN THRUSTER
- ANCHOR WINCH

## TECHNICAL DATA

- Dimensions (L.W.A.) ..... 157 x 80 x 44 mm
- Casing material ..... Charged Nylon UL 94 HB
- Degree of protection ..... IP 65
- Weight (battery included) ..... ≈340 g max
- Operating and storage temperature ..... -25°C - +70°C / -40°C - +85°C
- Operating frequency ..... I.S.M. 2.4 GHz, 16 ch
- Number of programmable channels ..... 16
- Transmission Mode ..... Half Duplex
- Autonomy at 20°C ..... ≈18 hours

## SUPPLY KIT

- 1 TRANSMITTING UNIT
- 1 RECEIVER UNIT
- 2 RECHARGEABLE LI-ON BATTERY
- 1 BATTERY CHARGER
- 1 USER MANUAL

### Flexball Italiana S.r.l.

Via San Luigi 13/A - 10043 Orbassano (To) - Italy

Tel 0039.011 90.38.900 - Fax 0039.011 90.38.747

info@flexballitaliana.com

www.flexballitaliana.com

**FLEXBALL**  
ITALIANA

WR CONTROLS GROUP

